

Osman Gazi Bridge protected for the long-term

ELIMINATOR[®] waterproofing system protects essential transportation link



Project	Osman Gazi Bridge, Turkey
Client	Turkish State of General Directorate of Highways
Contractor	IHI E&C
Authorised Contractor	ERSE Teknolojik Yapı Endüstri A.Ş.
(Waterproofing Applicator)	
GCP Solutions	ELIMINATOR [®] system, SAFETRACK [®] HW high friction surfacing system

Project

Revolutionising travel in the region

Built over the Sea of Marmara in Turkey's Izmit Bay between 2013–2016, the Osman Gazi Bridge, or “Izmit Bay Bridge,” as it is often referred to, is the fourth longest suspension bridge in the world.

Spanning more than 1.5km, the bridge's construction revolutionised travel between the north and south of the country, enabling passengers to make the journey across the sea in just three minutes instead of taking the one-hour ferry ride or the high-traffic 100km detour over land. The bridge opened to service in June 2016.

The bridge has become a highly trafficked route through the country, both for Turkish locals and for global businesses to transport their goods between Asia and Europe.



Long-lasting protection for new bridge

Waterproofing on the Osman Gazi Bridge needed to offer tough, durable and long-lasting protection in order to reduce the need for future maintenance. Given the time limitations on the construction work and the nature of the structure, the selected bridge deck waterproofing system needed to not only provide proven long lasting protection, but allow quick and easy application and importantly, it needed to have minimal environmental impact over its lifetime.

Speed and ease of application

KGM specified the **ELIMINATOR®** system from Stirling Lloyd (now GCP Applied Technologies) for the bridge deck waterproofing, based on numerous other high-profile collaborations.


Having worked on several major projects in the country over the past thirty years, Stirling Lloyd (now GCP Applied Technologies) was contracted by IHI E&C to take the lead on the waterproofing for the main central section of the bridge. The application process of the **ELIMINATOR**[®] system was completed within four weeks. In that time, Authorised Contractor Erse applied 76,000m², covering the entire central section of the bridge. In addition, the **SAFETRACK**[®] HW high friction surfacing system was applied on the bridge's walkways to provide a long lasting, anti-skid finish.

The speed and ease of application of the **ELIMINATOR**[®] system, together with the fact that each element of the system cures in under an hour, helped facilitate quick contract progression.

Based on unique **ESSELAC**[®] technology, **ELIMINATOR**[®] provides a tough, durable membrane that can withstand difficult site conditions. This will extend the service life of the bridge and reduce maintenance costs.

Blue360SM Total Business Advantage.

The power of GCP products, performance and people



North America customer service: 1-877-4AD-MIX (1-877-423-6491)

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP Applied Technologies (Malaysia) Sdn. Bhd, 7 Lorong CJ 1/1A, Off Jalan Balakong, 43200 Cheras Jaya, Kuala Lumpur, Malaysia

This document is only current as of the last updated date stated below and is valid only for use in Malaysia. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.my. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2022-01-31

gcpat.my/inspiration/project-profiles/osman-gazi-bridge-protected-for-the-long-term